

Cylinder padlock .316,AUS=LH25

With forced locking - key can only be extracted when locked

Product description

- Housing chrome-plated in brass
- Cylinder, nickel-plated brass satin
- Standard shackle clearance height 25 mm (AUS=LH25)
- Optionally with non-corroding shackles (AUS=LH25-NIRO)
- Other shackle heights (AUS=LH50, LH75, LH28/5)
- Steel shackle, diameter 8 mm, hardened and chrome-plated
- Steel shackle diameter 5 mm at shackle height 28 mm (AUS=LH28/5), hardened and chrome-plated
- Blocking wave (SW=), additional lateral scanning and security card depending on profile (PR=)
- Spherical / Tapered cylinder core head with reinforced key guide
- Core pins made of special wear-resistant bronze
- Standard version as per DIN EN 12320 class 3 (not valid for AUS=LH28/5)
- Optionally with hole for fastening a driving guard (VAR=1901043-X-BOHRUNG)
- Optionally available without forced locking (AUS2= OHNE ZWANGSSCHL)
- Optionally IP67 certified with protective cap (SUR=2)

Scope of delivery

- 1 cylinder padlock
- 2 nickel silver keys

Suitable ASSA ABLOY products

Order number	Product
8511	Maintenance spray
1090	Protective cap IP67

